

PREMEER vs. VINYL

COMPARISON

Premeer is manufactured with an e-beam cured topcoat for superior performance and increased benefits:

Premeer Performance & Benefit

Scratch/abrasion resistance. Reduced rejects/claims Moisture resistance Reduced rejects/claims

Boiling water/steam resistance Reduced claims

Resistance to stain, easier to clean Reduced rejects/claims Resistance to shrink and creep Reduced rejects/claims

Resistance to yellowing Reduced claims

Reduced laminatior rejects, laminator labor Easier to laminate (no primer)

4 times more film per roll = better yield Reduced roll changes, laminator lost time/ labor, waste,

transport costs, handling/storage costs & labor

No laminated boards sticking to each other. . . . Reduced waste/labor No discoloration at sharp edges & V groove . . . Reduced rejects

Recoatable surface. Increased customer appeal & manufacturing versatility

Print above substrate Increase customer appeal High print fidelity Increase customer appeal

Premeer Flat Lamination Vinyl Flat Lamination

Uses wet laminator/EVA glue Uses wet laminator/EVA glue

Laminates to PB/MDF/Plywood/gypsum. Laminates to PB/MDF/Plywood/gypsum DOES NOT need primer on back. DOES need primer on back for good bonding

Bonded directly to film Bonded to ink and primer 1.25 mil - 1.60 mil, more per roll 3.20 mil - 12.00 mil, less per roll

Less expensive More expensive

Premeer Moldings Vinyl Moldings

Uses Barbaran/Homag/other wrapping lines . . Uses Barbaran/Homag/other wrapping lines

Uses PUR hot melt glue, no paper backer Needs a paper backer Uses PEO hot melt glue, no paper backer Needs a paper backer

Premeer & the Environment Less material: 38 gsm to 74 gsm More material: 145+ gsm

Safest class of manmade films. Contains chlorine

Printed with water-based, VOC-free inks Printed with solvent inks

Recyclable film Not recyclable, classified as a hazardous material Incinerable film Not incinerable, classified as a hazardous material

Disposable in regular landfill Disposable in designated landfills only

Premeer Fire Rating ASTM E84/UL723 Vinyl Fire Rating Class A, best rating for flame spread/smoke . . . Variable, depending on manufacturer



Interprint, Inc. 101 Central Berkshire Blvd., Pittsfield, MA 01201 www.interprint.com www.premeer.com (413) 443-4733